tasker®

Multicolour cables



RoHS Conformity

Applications:
Flexible multicolour cables for wiring and electronics.

Characteristics:
Conductors: stranded in O.F.C. red copper
Cond. insulation: PVC
Core colours: White, Pink, Light-blue, Yellow, Bright-orange, Grey, Green, Red, Violet, Blue, Brown, Black

tasker® Code	Cond. number	Nominal section mm²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II) mt.	Type	Kg.	Conductor Resistance Ω/Km ± 5%	Max rated Voltage AC - V	Operative Temperature °C
C106	5	5 x 0,35 (22 AWG)	11x0,20	1,8		4,7	100	M	3,0	60	49	-15 / +70
C107	6	6 x 0,35 (22 AWG)	11x0,20	1,8		5,0	100	M	3,5	60	49	-15 / +70
C108	7	7 x 0,35 (22 AWG)	11x0,20	1,8		5,4	100	M	4,0	60	49	-15 / +70
C109	8	8 x 0,35 (22 AWG)	11x0,20	1,8		5,7	100	M	4,5	60	49	-15 / +70
C110	10	10 x 0,35 (22 AWG)	11x0,20	1,8		6,3	100	M	5,5	60	49	-15 / +70
C111	12	12 x 0,35 (22 AWG)	11x0,20	1,8		6,9	100	M	6,5	60	49	-15 / +70

Sheathed cables

RoHS Conformity

Applications:
Flexible sheathed cables for wiring and electronics.

Characteristics:
Conductors: stranded in O.F.C. red copper
Cond. insulation: PVC
Core colours: Brown, Blue, Black, Yellow/green, Red, White, Yellow, Grey, Bright-orange, Green, Violet, Pink, White/red, White/black, White/blue, White/green, White/brown, White/yellow, White/violet, Blue/red, Blue/black, Blue/green, Blue/brown, Blue/yellow
External Sheath: PVC
Sheath colour: Black

tasker® Code	Cond. number	Nominal section mm²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II) mt.	Type	Kg.	Conductor Resistance Ω/Km ± 5%	Max rated Voltage AC - V	Operative Temperature °C
C158	6	6 x 0,25 (23 AWG)	8x0,20	1,4		5,3	100	B	4,5	75	49	-15 / +70
C159	12	12 x 0,25 (23 AWG)	8x0,20	1,4		7,0	100	B	7,5	75	49	-15 / +70
C160	16	16 x 0,25 (23 AWG)	8x0,20	1,4		8,0	100	B	10,0	75	49	-15 / +70
C161	24	24 x 0,25 (23 AWG)	8x0,20	1,4		9,8	100	B	14,5	75	49	-15 / +70